S serisi

Halı Sıkma ve Kurulama Makinaları

Professional Carpet Spin And Dryer

Halı sıkma makinası, halı kurutma makinası yada santrifüj olarak bilinen Halı sıkma ve kurutma makinaları halı yıkama firmalarının olmazsa olmaz makinalarındandır. Halı yıkama işlemi sonrasına rulo şeklinde dürülmüş olan halılar makine içerisine yerleştirilir. İstenilen zaman aralığı ayarlandıktan sonra makine çalıştırılır .Ortalama 2-3 dakika süren sıkma işleminden sonra makine üzerinde bulunan zaman rölesi sayesinde otomatik olarak stop eder Sıkma işlemi sonucunda halılarda %98 e varan kuruluk sağlanmış olur.

Ardışık delik sistemine sahip olan paslanmaz iç tamburda yüksek devirde dönerek kurutulan halılarda su izi kalmaz, tek yöne doğru yüksek devirle dönen halı sıkma makinesi aynı zamanda halı tüylerini de ayrı yöne doğru taramış olur. Kullanılan yüksek kalite Avrupa Menşeili rulmanları. Güçlü ve yüksek devirli motorları, Firmamıza özel döküm yataklama sistemi, Doğru ve standartların da üzerinde kullanılan malzeme kalitesi, eşsiz merkezleme sistemi, zaman ayarlı kontrol panosu ile Halı sıkma makinelerimiz sınıfının en verimli, en sessiz ve en titreşimsiz makinelerinin başında gelmektedir.

Carpet spinning and drying machines are known to be the indispensable machines of carpet washing companies.

After the carpet washing process, the carpets that have been rolled and placed in the machine. After setting the desired time interval, the machine will be started. Prosses will automatically stop due to the time relay on the machine after 2-3 minutes of squeezing. As a result of the squeezing process, 98% dryness is achieved.

The rustproof inner drum, which has a consecutive hole system, does not have a water mark on the surface when it is dried by turning at high speed, while the carpet spinning machine rotating at a high speed in one direction scans carpet hair in the same direction at the same time. Used high quality European roller bearings.

Our carpet-spin and dry machines are among the most productive, quietest and most vibration-free machines in the class with their powerful and high speed motors, special cast iron tilting system, accurate and standard material quality, unique centering system and time control panel.

TEKNİK ÖZELLİKLER Technical Supports	S1000T	S2300T	S2700EC	S2700T	S2700K	S2700K Pro	S3200T	S3200K	S4000T	S4000K	S4500T	S4500K
VOLTAJ / Voltage	220/380	220/380	380	380	380	380	380	380	380	380	380	380
MOTOR GÜCÜ	4 Hp	5,5 Hp	5,5 Hp	7,5 Hp	7,5 Hp	7,5 Hp	10 Hp	10 Hp	10 Hp	10 Hp	15 Hp	15 Hp
İÇ TAMBUR BOYU	1200 mm.	2300 mm.	2700 mm.	2700 mm.	2700 mm.	2700 mm.	3200 m	3200 m	4000 m	4000 m	4500 m	4500 m
İÇ TAMBUR ÇAPI	320 mm.	320 mm.	380 mm.	400 mm.	400 mm.	400 mm.	400 mm.	400 mm.	400 mm.	400 mm.	500 mm.	500 mm.
TAMBUR DEVRİ	1000 d/dk.	1100 d/dk.	1000 d/dk.	1200 d/dk.	1300 d/dk.	1700 d/dk.	1100 d/dk.	1200 d/dk.	1000 d/dk.	1000 d/dk.	1000 d/dk.	1000 d/dk.
AYAK SİSTEMİ	Tekerlekli	Tekerlekli	Tekerlekli	Tekerlekli	Körüklü	Körüklü	Tekerlekli	Körüklü	Tekerlekli	Körüklü	Tekerlekli	Körüklü
BOYUTLAR (E-B-Y)	100x100x160 cm.	100x100x270 cm.	110x110x320cm.	120x110x330 cm.	120x120x330 cm.	120x120x1330 cm.	120x120x370 cm.	120x120x370 cm.	120x120x450 cm.	120x120x450 cm.	140x140x480 cm.	140x140x480 cm.
AĞIRLIK	150 Kg.	270 Kg.	320 Kg.	400 Kg.	460 Kg.	850 Kg.	510 Kg	580 Kg.	630 Kg.	730 Kg.	900 Kg.	980 Kg.

İstenilen özellik ve ebatlarda makina imalatımız vardır

We have different kinds of machine manufacturing according to technical specifications